

**GLOSS  
FINISH**

• TRUSTED QUALITY SINCE 1921 •

**RUST-OLEUM®**

## PORCH & FLOOR COATING



**URETHANE  
FORTIFIED  
ACRYLIC FORMULA**

REPELS WATER • RESISTS SCUFFING, FADING, CRACKING & PEELING

NET WT 128 FL OZ

PURE WHITE GLOSS

ONE GALLON

Rust-Oleum® Porch & Floor Coating offers outstanding performance. It's oil modified acrylic urethane fortified formula is engineered to provide superior color retention, adhesion and protection against UV rays, water damage and mildew on both wood and concrete surfaces. Rust-Oleum® Porch & Floor Coating protects and beautifies wood and concrete with deeply pigmented, opaque color in a gloss finish that enhances substrate texture and provides excellent coverage over new or previously coated surfaces.

The acrylic formula is boosted with polyurethane to optimize durability, add coating film flexibility and further increase water repellency, which helps maximize resistance to scuffing, fading, cracking and peeling. Its scrape and scuff-resistant finish stands up to heavy foot traffic and furniture abrasion, while its mildew resistant coating minimizes mildew staining.

### READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

**WHERE TO USE:** USE ON INTERIOR AND EXTERIOR WOOD OR CONCRETE SURFACES. NOT FOR USE ON GARAGE FLOORS.

**Wood Types:** Use on all species of pressure-treated lumber, Pine, Fir, Hemfir, Cypress, Cedar, Redwood, Poplar, Hickory and other North American hardwoods. Ideal for weathered wood where hiding signs of aging is desired. Can also be used on concrete patios and walkways.

### SURFACE PREPARATION:

**On Wood: Previously coated, weathered wood:** For best results, previous coatings such as paints, solid color and semi-transparent stains in a weathered state should be stripped to create a bare, sound surface for maximum coating adhesion and durability.

**Uncoated, weathered wood:** Before staining, bare, weathered wood must be thoroughly cleaned to remove ground-in dirt, mildew, mold and algae stains, gray, UV-damaged wood fibers and any other surface contaminants.

**Uncoated, new wood:** It is important to open wood pores and remove any surface barrier which would prevent the proper penetration or adhesion of a new coating by cleaning with a deck or wood cleaner.

After preparation, conduct a **Splash Test** – to conduct a Splash Test, sprinkle several handfuls of water on a few distinct areas of the bare wood surface. If the water absorbs rapidly, the surface is ready to be coated. If the water beads, puddles or is not absorbed, an internal or external barrier exists and must be eliminated before painting can begin.

**On Concrete: Bare Concrete:** Proper surface preparation is critical to performance. Before coating bare concrete surfaces, remove grease, oil, salt and other contaminants with EPOXYShield® HEAVY-DUTY DEGREASER (sold separately). Follow label instructions carefully. If necessary, use a wire brush or sander to remove any loose or unsound concrete or masonry. For proper penetration and maximum adhesion, use EPOXYShield® CONCRETE ETCH (sold separately). Follow label instructions carefully and allow the floor to dry completely. Wipe your fingers over the clean, dry surface. If you see any dust or powder on your fingers, repeat rinsing and scrubbing until the floor is clean.

**Previously Painted, Stained or Sealed Concrete:** Use a wire brush to remove any loose or peeling paint, stain or sealer. To ensure proper adhesion, scuff sand the entire surface. Wash the entire floor with EPOXYShield® HEAVY-DUTY DEGREASER (diluted as stated on the label) and scrub the surface using a stiff bristle brush or broom. Spot etch all exposed concrete surfaces using EPOXYShield® CONCRETE ETCH (sold separately). Rinse thoroughly and allow to dry completely.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN YOUNG CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**APPLICATION:** Rust-Oleum® Porch and Floor Coating is ready to use. Do not thin. This product is self priming. For the most durable finish apply two coats at the recommended coverage rate (see below). First coat will dry to touch in 1-2 hours. A minimum 4-6 hours dry time after first coat is recommended. Use only when air (ambient) temperature is 50-90°F (10-32°C) and relative humidity is below 85%. Do not paint outdoors if rain is expected within 24 hours. Apply with a high quality nylon/polyester bristle brush, short nap paint/stain pad or roller or an airless sprayer (do not use a pump sprayer). Brushing is the preferred method, especially for rough sawn wood. When rolling or spraying, make sure to back-brush along the grain, this will eliminate any drips, runs, uneven coverage or surface puddles. To minimize lap marks maintain a wet edge.

If using more than one gallon, intermix all cans of the same product to ensure color uniformity. Stir thoroughly before applying. **Note: Painted floors may be slippery when wet. If desired, EPOXYShield® ANTI-SKID ADDITIVE (sold separately) may be added to the mixed coating.**

**COVERAGE:** Each gallon covers approximately 430-530 sq ft/gal of smooth, bare surface.

**DRY TIME:** Because temperatures and humidity fluctuate, allow a minimum 24 hours dry before light foot traffic and 72 hours before returning furniture to deck/porch floor. Avoid dragging furniture across surface. On newly coated surfaces, allow 7 days cure before washing.

**CLEAN UP:** Wash tools and equipment with warm water and a mild detergent immediately after use. To remove dried product use lacquer thinner. Clean up over-spray, drips or spatters with water IMMEDIATELY, as dried paint is very difficult to remove. Properly dispose of all soiled rags and protect unused product from freezing.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: PROPYLENE GLYCOL AND N-METHYL PYRROLIDONE.** MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. **USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

**¡ADVERTENCIA!**  
**¡IRRITANTE! ES DAÑO SI SE INGERE. CONTIENE: PROPYLENGLICOL Y N-METIL PIRROLIDONA.** PUEDE CAUSAR IRRITACION DE OJOS, NARIZ Y GARGANTA. EVITE EL CONTACTO CON LA PIEL Y OJOS Y EVITE RESPIRAR LOS VAPORES Y EL ROCÍO. UTILICE PROTECCIÓN PARA LOS OJOS Y ROPA PROTECTORA. **USAR ÚNICAMENTE CON VENTILACIÓN ADECUADA.** Para evitar respirar los vapores y el rocío, abra ventanas y puertas o use otras medidas para asegurar la entrada de aire fresco durante la aplicación y secado. Si siente lagrimeo, dolor de cabeza o mareo, incremente el aire fresco. Si se usa correctamente, un respirador (NIOSH aprobado para vapor orgánico, de serie P pre-filtrado particulado) podría ofrecer protección adicional; obtenga información profesional antes de usar. **PRIMEROS AUXILIOS:** Si tiene dificultad al respirar, alejese y obtenga aire fresco. Si continúan las dificultades obtenga ayuda médica de inmediato. En caso de contacto con los ojos, enjuague rápidamente con suficiente agua por lo menos 15 minutos y obtenga atención médica; para la piel, lave completamente con agua y jabón. Si se ingiere, obtenga atención médica de inmediato. **¡ADVERTENCIA!** Es sabido para el estado de California, que este producto contiene químicos que pueden causar cáncer y defectos al nacer u otros defectos reproductivos. **PRECAUCIÓN: NO SE DEJE AL ALCANCE DE LOS NIÑOS – NO LO INGERA.** HECHO EN E.U.A.

**CATEGORY:** WATERPROOFING SEALER  
Max VOC 100 g/L (.8 lbs./gal.)

**SATISFACTION GUARANTEED:** If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-888-NUFLOOR (1-888-683-5667)

**RUST-OLEUM®**  
CORPORATION  
11 Hawthorn Pkwy., Vernon Hills, IL 60061

An RPM Company

1-800-481-4785  
[rustoleum.com](http://rustoleum.com)

©2007 Rust-Oleum Corporation  
Made in USA L244853R 0807

PURE WHITE GLOSS 244853



0 20066 17222 0